



Pro Fuel Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 29/08/2016 Revision date: 15/11/2021 Supersedes version of: 15/06/2021 Version: 1.4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Name : Pro Fuel Cleaner
UFI : 9E2E-K5GN-3D91-RAPV
Product code : 1036B
Product group : Trade product
Article number : 1036B

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Industrial/Professional use spec : Professional use.
Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

BARDAHL NL - OCD NEDERLAND BV
Maxwellstraat 41
3316 GP Dordrecht
Nederland
T 0031 78 651 2322 - F 0031 78 617 4848
mjkooijman@bardahl.nl - www.bardahl.nl

1.4. Emergency telephone number

Emergency number : +31 (0) 6 54924171
During office hours: 8.30 t/m 17:00 h

Country	Official advisory body	Address	Emergency number	Comment
	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	0870 243 2241	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity – Single exposure, Category 3, H336
Narcosis
Specific target organ toxicity – Single exposure, Category 3, H335
Respiratory tract irritation
Specific target organ toxicity – Repeated exposure, Category 2 H373

Pro Fuel Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Aspiration hazard, Category 1 H304

Hazardous to the aquatic environment – Chronic Hazard, Category 2 H411

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Contains

: xylene; propan-2-ol; isopropyl alcohol; isopropanol; Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes

Hazard statements (CLP)

: H225 - Highly flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H335 - May cause respiratory irritation.
H336 - May cause drowsiness or dizziness.
H373 - May cause damage to organs through prolonged or repeated exposure.
H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, open flames, sparks. – No smoking.
P233 - Keep container tightly closed.
P260 - Do not breathe vapours.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, eye protection/face protection.
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P331 - Do NOT induce vomiting.
P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P501 - Dispose of contents/container to a hazardous or special waste collection point.
Extra phrases : For professional users only.

Extra phrases

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

Pro Fuel Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
xylene (Note C)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216-32	20 – 40	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
propan-2-ol; isopropyl alcohol; isopropanol	CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0 REACH-no: 01-2119457558-25	20 – 40	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes	EC-No.: 927-510-4 REACH-no: 01-2119475515-33	15 – 30	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
4-methylpentan-2-ol; methyl isobutyl carbinol	CAS-No.: 108-11-2 EC-No.: 203-551-7 EC Index-No.: 603-008-00-8 REACH-no: 01-2119473979-13	5 – 15	Flam. Liq. 3, H226 Eye Irrit. 2, H319 STOT SE 3, H335
ethylbenzene	CAS-No.: 100-41-4 EC-No.: 202-849-4 EC Index-No.: 601-023-00-4 REACH-no: 01-2119489370-35	1 – 10	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated light	CAS-No.: 64742-47--8 EC-No.: 265-149-8 REACH-no: 01-2119484819-18	1 – 3	Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Poly[oxy(1,2-propanedyl), alpha-(3-aminopropyl)-omega-hydroxy-C12-15 alkyl ethers	EC-No.: POLYMER	< 1	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
toluene	CAS-No.: 108-88-3 EC-No.: 203-625-9 EC Index-No.: 601-021-00-3 REACH-no: 01-2119471310-51	< 0.3	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
Poly[oxy(1,2-propanedyl)], alpha-propyl-omega-hydroxy-C12-15 alkyl ethers	EC-No.: POLYMER	< 0.1	Skin Irrit. 2, H315 Eye Dam. 1, H318
naphthalene	CAS-No.: 91-20-3 EC-No.: 202-049-5 EC Index-No.: 601-052-00-2	< 0.1	Flam. Sol. 2, H228 Acute Tox. 4 (Oral), H302 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Pro Fuel Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
4-methylpentan-2-ol; methyl isobutyl carbinol	CAS-No.: 108-11-2 EC-No.: 203-551-7 EC Index-No.: 603-008-00-8 REACH-no: 01-2119473979-13	(25 ≤ C ≤ 100) STOT SE 3, H335

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If medical advice is needed, have product container or label at hand.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	: Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness. May cause damage to organs (kidneys, central nervous system, liver) through prolonged or repeated exposure.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Carbon dioxide. Water haze. Dry powder. Foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour.
Hazardous decomposition products in case of fire	: Incomplete combustion will generate poisonous carbon monoxide, carbon dioxide and other toxic gases.

5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Prevent liquid from entering sewers, watercourses, underground or low areas.

Pro Fuel Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. Eliminate every possible source of ignition. Ensure adequate ventilation, especially in confined areas.

6.1.1. For non-emergency personnel

Emergency procedures : Keep public away from danger area.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

6.2. Environmental precautions

Dam up the liquid spill. Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Recover the product with absorbent material.

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not eat, drink or smoke when using this product.

Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Provide local exhaust or general room ventilation.

Storage conditions : Store in a closed container. Store in a dry, cool and well-ventilated place.

Incompatible materials : Freezing. Open flame. Sources of ignition.

Special rules on packaging : Keep only in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

xylene (1330-20-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	221 mg/m ³ (Xylene, mixed isomers, pure; EU; Timeweighted average exposure limit 8 h; Indicative occupational exposure limit value)
IOEL TWA [ppm]	50 ppm (Xylene, mixed isomers, pure; EU; Timeweighted average exposure limit 8 h; Indicative occupational exposure limit value)

Pro Fuel Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

xylene (1330-20-7)	
IOEL STEL	442 mg/m ³ (Xylene, mixed isomers, pure; EU; Short time value; Indicative occupational exposure limit value)
IOEL STEL [ppm]	100 ppm (Xylene, mixed isomers, pure; EU; Short time value; Indicative occupational exposure limit value)
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	983 mg/m ³
IOEL TWA [ppm]	400 ppm
IOEL STEL	1230 mg/m ³
IOEL STEL [ppm]	500 ppm
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	999 mg/m ³ Propan-2-ol; United Kingdom; Timeweighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
WEL TWA (OEL TWA) [2]	400 ppm Propan-2-ol; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
WEL STEL (OEL STEL)	1250 mg/m ³ Propan-2-ol; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
WEL STEL (OEL STEL) [ppm]	500 ppm Propan-2-ol; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
ethylbenzene (100-41-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	442 mg/m ³ (Ethylbenzene; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
IOEL TWA [ppm]	100 ppm (Ethylbenzene; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
IOEL STEL	884 mg/m ³ (Ethylbenzene; EU; Short time value; Indicative occupational exposure limit value)
IOEL STEL [ppm]	200 ppm (Ethylbenzene; EU; Short time value; Indicative occupational exposure limit value)
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	441 mg/m ³ Ethylbenzene; United Kingdom; Timeweighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
WEL TWA (OEL TWA) [2]	100 ppm Ethylbenzene; United Kingdom; Timeweighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
WEL STEL (OEL STEL)	552 mg/m ³ Ethylbenzene; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
WEL STEL (OEL STEL) [ppm]	125 ppm Ethylbenzene; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)

Pro Fuel Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

toluene (108-88-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	192 mg/m ³ (Toluene; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
IOEL TWA [ppm]	50 ppm (Toluene; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
IOEL STEL	384 mg/m ³ (Toluene; EU; Short time value; Indicative occupational exposure limit value)
IOEL STEL [ppm]	100 ppm (Toluene; EU; Short time value; Indicative occupational exposure limit value)
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	191 mg/m ³ Toluene; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
WEL TWA (OEL TWA) [2]	50 ppm Toluene; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
WEL STEL (OEL STEL)	384 mg/m ³ Toluene; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
WEL STEL (OEL STEL) [ppm]	100 ppm Toluene; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
naphthalene (91-20-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	52 mg/m ³
IOEL TWA [ppm]	10 ppm
IOEL STEL	79 mg/m ³
IOEL STEL [ppm]	15 ppm
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	50 mg/m ³

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment:

Protective goggles. Gloves.

Pro Fuel Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection			
Type	Field of application	Characteristics	Standard
tightly fitting safety goggles			EN 166

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Safety gloves					EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:

Ensure good ventilation of the work station

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Appearance	: clear.
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: < 10 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: 1 – 3
Viscosity, kinematic	: < 20.5 mm ² /s (40°C)
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 0.787 – 0.797 g/cm ³ 20°C
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

Pro Fuel Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Open flame. Sparks. Heat. Water, humidity. Freezing.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

xylene (1330-20-7)	
LD50 oral rat	4300 mg/kg
LD50 dermal rabbit	2000 mg/kg
LC50 Inhalation - Rat	6350 mg/l/4h
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 Inhalation - Rat	> 20 mg/l/4h
Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes	
LD50 oral rat	> 5840 mg/kg
LD50 dermal rat	> 2920 mg/kg
LC50 Inhalation - Rat	> 23300 mg/l/4h
ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg

Pro Fuel Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethylbenzene (100-41-4)	
LD50 dermal rabbit	15415 mg/kg
LC50 Inhalation - Rat	17.8 mg/l/4h
LC50 Inhalation - Rat [ppm]	4000 ppm/4h
toluene (108-88-3)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	12223 mg/kg
LC50 Inhalation - Rat	> 20 mg/l/4h
naphthalene (91-20-3)	
LD50 oral rat	2600 mg/kg
LD50 dermal rat	> 2500 mg/kg
Skin corrosion/irritation	: Causes skin irritation. pH: 1 – 3
Serious eye damage/irritation	: Causes serious eye irritation. pH: 1 – 3
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
toluene (108-88-3)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness. May cause respiratory irritation.
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
STOT-single exposure	May cause drowsiness or dizziness.
Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes	
STOT-single exposure	May cause drowsiness or dizziness.
4-methylpentan-2-ol; methyl isobutyl carbinol (108-11-2)	
STOT-single exposure	May cause respiratory irritation.
Distillates (petroleum), hydrotreated light (64742-47--8)	
STOT-single exposure	May cause drowsiness or dizziness.
toluene (108-88-3)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
ethylbenzene (100-41-4)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
toluene (108-88-3)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Pro Fuel Cleaner	
Viscosity, kinematic	< 20.5 mm ² /s (40°C)

Pro Fuel Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

xylene (1330-20-7)

LC50 - Other aquatic organisms [1]	8.9 – 16.4 mg/l (Pimephales promelas 96h)
EC50 - Crustacea [1]	3.2 – 9.5 mg/l (Daphnia magna) (48h)

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)

LC50 - Fish [1]	9640 mg/l (Pimephales promelas)
LC50 - Other aquatic organisms [1]	> 10000 mg/l Daphnia magna
EC50 - Crustacea [1]	> 9700 mg/l (24h)
EC50 - Other aquatic organisms [1]	> 1000 mg/l (Algen 72h)

Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes

EC50 - Crustacea [1]	3 mg/l
----------------------	--------

ethylbenzene (100-41-4)

LC50 - Fish [2]	4.2 mg/l
-----------------	----------

toluene (108-88-3)

LC50 - Fish [1]	24 mg/l Salmo gairdneri (Oncorhynchus mykiss)
LC50 - Fish [2]	13 mg/l Lepomis macrochirus
EC50 - Crustacea [1]	84 mg/l Locomotor effect
EC50 - Crustacea [2]	11.5 – 19.6 mg/l
Threshold limit - Algae [1]	> 400 mg/l Scenedesmus quadricauda; toxicity test
Threshold limit - Algae [2]	105 mg/l Microcystis aeruginosa

naphthalene (91-20-3)

LC50 - Fish [1]	0.51 mg/l
EC50 - Crustacea [1]	3.4 mg/l

12.2. Persistence and degradability

xylene (1330-20-7)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)

Persistence and degradability	Product is biodegradable.
Biodegradation	98 %

Pro Fuel Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethylbenzene (100-41-4)	
Persistence and degradability	Readily biodegradable.
Biochemical oxygen demand (BOD)	1.44 g O ₂ /g substance
Chemical oxygen demand (COD)	2.1 g O ₂ /g substance
ThOD	3.17 g O ₂ /g substance
BOD (% of ThOD)	45.4 % ThOD

toluene (108-88-3)	
Persistence and degradability	Readily biodegradable.
Biochemical oxygen demand (BOD)	2.15 g O ₂ /g substance
Chemical oxygen demand (COD)	2.52 g O ₂ /g substance
ThOD	3.13 g O ₂ /g substance
BOD (% of ThOD)	0.69 % ThOD

naphthalene (91-20-3)	
Persistence and degradability	Inherently biodegradable.

12.3. Bioaccumulative potential

xylene (1330-20-7)	
BCF - Fish [2]	7 – 26
Bioconcentration factor (BCF REACH)	< 500
Partition coefficient n-octanol/water (Log Pow)	3.2

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
Partition coefficient n-octanol/water (Log Pow)	0.05
Bioaccumulative potential	not bioaccumulable.

ethylbenzene (100-41-4)	
BCF - Fish [1]	1
BCF - Fish [2]	15 – 79
BCF - Other aquatic organisms [1]	4.68
Bioconcentration factor (BCF REACH)	< 500
Partition coefficient n-octanol/water (Log Pow)	3.15

toluene (108-88-3)	
BCF - Fish [1]	13.2 <i>Anguilla japonica</i>
BCF - Fish [2]	90 72h; <i>Leuciscus idus</i>
BCF - Other aquatic organisms [1]	380 24h; <i>Chlorella</i> sp; Fresh weight
BCF - Other aquatic organisms [2]	4.2 4.2; <i>Mytilus edulis</i> ; Fresh weight
Partition coefficient n-octanol/water (Log Pow)	2.73 Experimental value
Bioaccumulative potential	Low.

12.4. Mobility in soil

xylene (1330-20-7)	
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.

Pro Fuel Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethylbenzene (100-41-4)	
Surface tension	0.029 N/m
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	PCKOCWIN v1.66; 2.71; Calculated value; Koc; PCKOCWIN v1.66; 517.8; Calculated value
toluene (108-88-3)	
Surface tension	0.03 N/m (20°C)

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of this material and its container at hazardous or special waste collection point.
Sewage disposal recommendations	: Do not discharge into drains or the environment.
Product/Packaging disposal recommendations	: Collect all waste in suitable and labelled containers and dispose according to local legislation.
Additional information	: Empty the packaging completely prior to disposal. Do not re-use empty containers.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

In accordance with / / / ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1993	UN 1993	UN 1993	UN 1993	UN 1993
14.2. UN proper shipping name				
FLAMMABLE LIQUID, N.O.S.	FLAMMABLE LIQUID, N.O.S.	Flammable liquid, n.o.s.	FLAMMABLE LIQUID, N.O.S.	FLAMMABLE LIQUID, N.O.S.
Transport document description				
UN 1993 FLAMMABLE LIQUID, N.O.S. (propan-2-ol; isopropyl alcohol; isopropanol ; Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes), 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 1993 FLAMMABLE LIQUID, N.O.S. (propan-2-ol; isopropyl alcohol; isopropanol ; Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes), 3, II, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1993 Flammable liquid, n.o.s. (propan-2-ol; isopropyl alcohol; isopropanol ; Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes), 3, II, ENVIRONMENTALLY HAZARDOUS	UN 1993 FLAMMABLE LIQUID, N.O.S. (propan-2-ol; isopropyl alcohol; isopropanol ; Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes), 3, II, ENVIRONMENTALLY HAZARDOUS	UN 1993 FLAMMABLE LIQUID, N.O.S. (propan-2-ol; isopropyl alcohol; isopropanol ; Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes), 3, II, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
3	3	3	3	3

Pro Fuel Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.4. Packing group				
II	II	II	II	II
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 274, 601, 640D
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02, R001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T7
Portable tank and bulk container special provisions (ADR)	: TP1, TP8, TP28
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 2
Special provisions for carriage - Operation (ADR)	: S2, S20
Hazard identification number (Kemler No.)	: 33
Orange plates	:
Tunnel restriction code (ADR)	: D/E
EAC code	: •3YE

Transport by sea

Special provisions (IMDG)	: 274
Limited quantities (IMDG)	: 1L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T7
Tank special provisions (IMDG)	: TP1, TP28, TP8
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: B

Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A3

Pro Fuel Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ERG code (IATA) : 3H

Inland waterway transport

Classification code (ADN) : F1
Special provisions (ADN) : 274, 601, 640D
Limited quantities (ADN) : 1 L
Excepted quantities (ADN) : E2
Equipment required (ADN) : PP, EX, A
Ventilation (ADN) : VE01
Number of blue cones/lights (ADN) : 1

Rail transport

Classification code (RID) : F1
Special provisions (RID) : 274, 601, 640D
Limited quantities (RID) : 1L
Excepted quantities (RID) : E2
Packing instructions (RID) : P001, IBC02, R001
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T7
Portable tank and bulk container special provisions (RID) : TP1, TP8, TP28
Tank codes for RID tanks (RID) : LGBF
Transport category (RID) : 2
Colis express (express parcels) (RID) : CE7
Hazard identification number (RID) : 33

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

Ensure all national/local regulations are observed

Pro Fuel Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Indication of changes

Section	Changed item	Change	Comments
1.1	Product code	Modified	
1.1	Other means of identification	Modified	

Abbreviations and acronyms:

Abbreviations and acronyms:

RID: Regulations Concerning the International Transport of Dangerous Goods by Rail

ICAO: International Civil Aviation Organization

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Flam. Sol. 2	Flammable solids, Category 2
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.

Pro Fuel Cleaner

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.